

COMBINATION WELDED FABRIC
 1/2" x 3" - 2" x 2" G.A.W./PVC
 COATED AVAILABLE

RAIL TIE SPACING 24"

2" OVERLAP

1/2" x 3" x 10-1/2 GA.
 NO CLIMB WIRE MESH
 GALVANIZED OR PVC
 COATED

1.625 x 1.25
 RAILS

COVER STRAP

2" x 2" x 8 GA. NO
 CLIMB WIRE MESH
 GALVANIZED OR
 PVC COATED

4" OD TERMINAL POST AND
 3.25 x 2.50 'C' SECTION LINE POSTS
 SPACED 7'-0" O.C. DEPENDING ON
 APPLICATION OF WIND LOAD
 SPECIFIED IN M.P.H.

10" x 36" ANTI-DIG GRID 1/2" x 3" x
 10 1/2 GA. PVC COATED OR 18"
 BURIED VERTICAL

3/16 x 2" STEEL
 COVER STRAP
 W/SLOTS 12" OC

3" OVERLAP ON
 WELDED WIRE PANEL

3.25" x 2.50" ROLL
 FORMED 'C' SECTION POST

3/8 x 4 1/2"
 BOLT & NUT-12" OC

1/2"

4" OVERLAP

2"

2"

14"

END/CORNER CONNECTION

ITEM	QNTY	DESCRIPTION		MATERIAL
		MACHINING TOLERANCES		FABRICATION TOLERANCES
SCALE	NONE	CHK'D BY	DTM	0.1 ± 0.030 UNDER 1.8" ± 1/32
				0.02 ± 0.015 1.8" AND OVER ± 1/16
				± 0.005 ALL MACHINED SURFACES ± 1/16
				ANGLES ± 1/16 BREAK ALL SHARP EDGES
DWN BY DTM 04-01-17 APP'D BY				
SUPER 'C' with BARB WIRE, ROUND TERM. COVER STRAPS (WELDED WIRE)				
CAD FILENAME: FENCE 4-9		GREGORY FENCE		REF. No. DRWG No.
LAST PLOT DATE: 09/01/17		4100 13th Street SW Canton, Ohio 44710		FENCE 4-9