

STRUT

MANUFACTURED
TO LENGTH

ACCESSORIES

ROOFTOP
SUPPORT BLOCKS

THREADED
ROD

S M A R T

SELLING


Equipping your team with a high-level review of Gregory Strut Products



Continuous roll formed close-tolerance channel

G-STRUT metal framing channels meet or exceed industry standards and are available in all profile sizes, perforations, weld configurations & finishes:

- Pre-galvanized, G90 zinc coating, 33,000 MY standard (Conforms ASTM 653)
- HDG 'batch galvanized' heavy zinc coating (ASTM 123)
- Plain finish, Hot roll pickled steel (ASTM 1011)
- Stainless steel, Grades 304 & 316 (ASTM A-240)
- Painted finishes in standard green or custom colors; heat cured powder coating
- Back-to-back welded configurations



Cost & labor savings

- With labor in short supply, saves valuable time and labor costs in the field
- Manufactured to precise length; no wasted or discarded product

Quality & flexibility

- Clean shear cut on rolling mill – no sharp burrs or shavings
- Hold very tight tolerances – much greater precision than saw cuts
- Available in any size or fractional increment from 6" to 24 ft.
- No minimum order quantity requirement



Complete line of Hardware, Accessories, Fittings, Hangers & Supports suits every installation

- Flat plate connectors
- Angle fittings
- Conduit Clamps
- Brackets
- Braces
- Hardware
- Beam clamps
- Swivels and clevises
- Pipe & riser clamps

All accessories, hangers & supports are designed to construct your system in complete compatibility with G-STRUT metal framing strut channels



Roof blocks

Built for long life and superior performance, our heavy-duty rooftop supports provide durable, weather-resistant & eco-friendly installations for rooftop infrastructure.

- 100% recycled rubber/truck tires substrate
- UV resistant materials
- Green reflector for high visibility and safety
- Innovative design inhibits floating and shifting
- Freeze and thaw resistant
- LEED certifiable product
- Vibration dampening
- Compatible with most rooftop materials
- Standard with 13/16" PG channel
- Also available in custom risers, rollers and connected long channels



Increase Stability

An essential component to strut systems, G-STRUT threaded rod safely and securely suspends pipe, conduit, HVAC.

- Available in standard lengths including 6, 10 & 12 ft.
- Sizes include: 1/4" 5/16" 3/8" 1/2" 5/8" 3/4" 7/8" 1" 1-1/8" 1-1/4"
- Electrogalvanized (EG) standard
- Also available in plain, stainless steel & HDG



4100 13th St. SW, Canton, OH 44710 1-866-99STRUT

Gregory Strut is a division of Gregory Industries

LEARN MORE



gregorystrut.com